

HIGH PERFORMANCE AVIATION FIRE EXTINGUISHERS



HALOTRON® BrX (2-BTP) offers an innovative solution for Halon 1211 replacement. These extinguishers utilize Halotron® BrX to meet the latest aviation extinguisher standards. BrX is a low Global Warming Potential (GWP) and very low Ozone Depletion Potential (ODP) clean agent approved for commercial aircraft use. The extinguishers feature lightweight aluminum valves and cylinders (Model 351 has a steel cylinder). Models 349 and 351 include a hose that allows the operator greater maneuverability in tight spaces. Amerex provides the ideal solution for the aviation portable extinguisher needs.

**HALOTRON® BrX EXTINGUISHERS HAVE A 12-YEAR SERVICE LIFE
AND ARE NON-RECHARGEABLE**



LOW GWP AND VERY LOW ODP CLEAN AGENT

AGENT TYPE	HALOTRON® BrX (2-BTP)				
VALVE TYPE	Anodized Aluminum				
DESIGN	Nozzle			Hose & Nozzle	
MODEL NUMBER	A337TS	339	347TS	349TS	351
UL & ULC RATING	2B:C	5B:C	5B:C	5B:C	2A:10B:C
CAPACITY (LBS.) / (KG)	1.79 / .81	3.55 / 1.6	3.75 / 1.7	3.75 / 1.7	12.5 / 5.67
FILLED WT. (LBS.) / (KG)	3.04 / 1.38	5.1 / 2.31	5.50 / 2.49	5.75 / 2.61	19.88 / 9.02
HEIGHT (IN.) / (MM)	11.25 / 285.75	13.69 / 347.66	17.59 / 446.9	17.59 / 446.9	20.25 / 514.3
WIDTH (IN.) / (MM)	4 / 101.6	4.13 / 104.78	4 / 101.6	5.88 / 149.35	8.5 / 215.9
DEPTH (IN.) / (MM)	3.25 / 82.6	3.5 / 88.9	3.25 / 82.6	3.25 / 82.6	5 / 127
DISCHARGE TIME (SEC.)	9	8	9	9	16
RANGE (INITIAL- FT. / M)	7-8 / 2.1-2.4	11-12 / 3.4-3.7	10-12 / 3.1-3.7	10-12 / 3.1-3.7	15-17 / 4.6-5.2
MINIMUM CONFINED SPACE REQUIREMENTS (FT³ / M³)	427 / 12.09	849 / 24.04	896 / 25.37	896 / 25.37	2,988 / 84.6
NOMINAL OPERATING PRESSURE	90 PSIG / 6.2 BAR	100 PSIG / 6.9 BAR	100 PSIG / 6.9 BAR	100 PSIG / 6.9 BAR	150 PSIG / 10.3 BAR
FAA APPROVED MODEL	Yes	Yes	Yes	Yes	Yes
INCLUDED BRACKET	Aircraft				*

CEDiSS

FEATURES & BENEFITS

- **6-Year manufacturer's warranty**
- Aluminum cylinders (Model 351 has a steel cylinder)
- Durable high-gloss polyester powder paint
- All-metal valve construction
- Hose is unique to Amerex product (Models 349 and 351)
- Hose provides greater access to tight spaces—offering greater flexibility when using the extinguisher (Models 349 and 351)
- Temperature range -40°F to 120°F
- Models A337, 339, 347TS, 349TS and 351 are FAA approved in accordance with DOT/FAA/AR-01/37
- Maximum visibility during discharge
- No electrical conductivity back to the operator
- No thermal or static shock
- Leaves no residue
- QR coded and multilingual labels
- EPA approved "clean agent" for Class A, B and C hazards
- Low GWP – 0.26 (100 year)
- Low ODP – 0.0028
- Short atmospheric lifetime

***MODEL 809 BRACKET
FOR THE MODEL 351
EXTINGUISHER
SOLD SEPARATELY.**

**MANUFACTURED AND TESTED
TO UL STANDARDS**
COMPLIES WITH NFPA 10 STANDARD
ISO-9001 AND ISO-14001 CERTIFIED
UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S508 - UL 2129 &
CAN/ULC-S566 - UL 711

7595 Gadsden Hwy.
P.O. Box 81
Trussville, AL 35173

Ph (205) 655-3271
customer.service@amerex-fire.com
intl.sales@amerex-fire.com

www.amerex-fire.com
webstore.amerex-fire.com

Quality is Behind the Diamond®